

Part # 38-4340 Arc Knight® Overall

Weldas® Arc Knight® Overalls are made with a combination of grey Heavy Duty 16 oz. FR Cotton and black split cowhide. This garment is designed to withstand medium to heavy duty welding applications and keep fab shop workers clean, productive and protected. Overall straps are stretchable as well as built in elastic at the waist. This athletic feature provides "give" when bending up and down and removes restrictions normal weld garments don't consider in the everyday work environment. Many other innovative features such as the flap covered chest pocket, zippered opening for boot entry, enclosed side pockets and many others were incorporated for the practicality of the professional welder and worker.



Applications

Light, Medium, Heavy Duty Welding

Testing



Features & Benefits

- Material: Heavy Duty 16 oz. FR Cotton, premium black split cowhide, Kevlar® sewn
- Safety Features: Stretchable overall straps w/ quick release buckles, stretchable waist, flap closed chest pocket, zippered/hook & loop boot entry

Part #	Size	UPC
38-4340M	Medium	726223243403
38-4340L	Large	726223343400
38-4340XL	XLarge	726223443407
38-4340XXL	2XLarge	726223543404



This product is in compliance with the regulation (EU) 2016/425



**WELDAS PRODUCT:
38-4340, 38-4350, 38-4375**

EN ISO 11611 (2015), Class 2/A1+A2



Clothing type: Arc Knight®

Trade mark: Arc Knight®

Size: see imprint on the product

Sizing according to: EN ISO 13688 (in CM).

	M	L	XL	2XL	3XL
EU	48	52	56	60	64
A	176	180	184	188	196
B	96	104	112	120	128
C	84	92	100	112	124
D	79	81	83	85	87
E	63	64	65	66	67

C = + 5 CM

Intended use:

General:

This product is intended to be used for all arc welding processes like MMA, MIG/MAG, TIG, micro plasma, spot and gas welding as well as plasma and oxygen cutting, gouging, brazing and thermal arc spraying. Because applications vary, it is the user's responsibility to identify the right product for each application.

Identified hazards:

With the welding processes of intended use the following hazards are identified: flames, spatter of molten material, radiant heat as well as short term electrical shock.

High voltage:

This product protects against short term electrical shock and not against long term high voltages! Welding and cutting machines can cause these so follow the safety instructions of the machines used as well! When there is an increased risk of shock or electrical live parts additional electrical isolation will be required as is indicated under 6.10 of the EN11611 for protection against live electrical conductors up to 100 V = (DC).

Body protection in all positions:

This product protects in certain positions of working and welding. It could be possible that extra protection products are required. It is the responsibility of the user to identify that.

Protection of aprons:

In case an apron is used the apron should, at least, protect the user from seam side to seam side

Additional garments:

Additional garments shall meet at least Class 1 of the EN11611.

Improper use:

Level of protection:

The level of protection will be reduced if the welders protective clothing is contaminated with flammable materials.

Level of oxygen:

Increase of oxygen in the air will reduce considerably the protection of the welders protective clothing against flame. Care should be taken when welding in confined places. Air enriched with oxygen will be dangerous!

Electrical isolation:

The electrical isolation provided by the clothing will be reduced when the clothing is wet, dirty or soaked in sweat.

Use of 2-piece clothing:

When 2-piece clothing is used both items shall be worn together to provide the specified level of protection

Additional body protection during welding:

Additional body protection used with this product during welding must meet the appropriate EN standard for welding hazards.

Limitations for use:

This flame retardant cotton / leather work clothing to be used for general labour activities as well as welding. User has to see to it that all closures are closed specially for use with welding applications and the choice of the right size. If molten metal stick to the clothing, the user needs to remove the clothing immediately. The user needs to wear the bib and brace always in combination with a welding jacket.

If the user observes symptoms similar to sunburn, UV radiation come through the product. In that case, the product needs to be repaired or replaced. The user should think about it that there might be more protective layers needed in the future.

Materials used:

Side split cowhide in combination with 520 gr/m² flame retardant fabric is used with 3 ply KEVLAR® for manufacturing this product as well as current isolated push buttons and hook and loop fastening materials for the closures and reinforcements. DuPont™ and KEVLAR® are trademarks or registered trademarks of E.I.duPont de Nemours and Company

Health information:

The pH, Chromium (VI) and PCP levels of all materials have been tested and meet CE health standards. Coloring: coloring is done by using natural materials

Washing, drying and ironing:

No washing, tumble drying and ironing is allowed.

Storage:

Store dry and at temperatures over 5° Celcius. Do not stack higher than 5 cartons on 1 pallet.

Ageing:

If washing, drying and ironing has been applied (which is not advised), or not stored according to the above instruction, the ageing of this product will be influenced negatively.

Warranty:

This product is warranted against manufacturing defects. If the product can be repaired, it needs to be done by the manufacturer.

Remove:

Once this product can't be used anymore, it is the responsibility of the user to remove this product in an environmental way. Disposal according to local regulations.

Durability: The service life depends on the degree of wear and use intensity in the respective application areas. Temporal information is therefore not possible.

Climate according to clause 6.10:

Conditioning and testing of the samples was carried out at a temperature of (20 ± 2) °C and relative humidity of (85 ± 5) %.

Attention:

Weldas gloves and clothing have been tested and certified at TÜV Rheinland LGA Products GmbH, Germany (EU no. 0197). For more information on EN standards, testing methods, test reports, product certifications, and other products, please e-mail us at: europa@weldas.eu or visit our web site: www.weldas.com

Address information Weldas:

Weldas Europe B.V. Blankenweg 18 4612 RC Bergen op Zoom The Netherlands e-mail: europa@weldas.eu



WELDAS PRODUCT:
38-4320, 38-4436, 38-4442,
38-4442 W, 38-4448, 38-4448 W
EN ISO 11611 (2015), Class 2/A1+A2

	Length CM	Width CM
38-4320	51	60
38-4436	91	60
38-4442	107	60
38-4442 W	107	80
38-4448	122	60
38-4448 W	122	80

The following explains the pictogram marked on this product:



General safety requirements

Subclause	Requirement	Class 1	Class 2
6.1	Tensile strength - woven outer textile material - leather	400 N 80 N	400 N 80 N
6.2	Tear strength	20 N	20 N
6.3	Burst strength	200 kPa	200 kPa
6.4	Seam strength - textile material - leather	225 N 110 N	225 N 110 N
6.5	Dimensional change of woven textile materials Dimensional change of knitted textile materials	$\leq \pm 3 \%$ $\leq \pm 5 \%$	$\leq \pm 3 \%$ $\leq \pm 5 \%$
6.6	Requirements for leather: fat content	$\leq 15 \%$	$\leq 15 \%$
6.7	Flame spread	ISO 15025:2000, Procedure A (surface ignition); ISO 15025:2000, Procedure B (edge ignition); No flaming to the top or either side edge No hole formation ^a No flaming or molten debris Mean afterflame ≤ 2 s Mean afterglow ≤ 2 s	ISO 15025:2000, Procedure A (surface ignition); ISO 15025:2000, Procedure B (edge ignition); No flaming to the top or either side edge No hole formation ^a No flaming or molten debris Mean afterflame ≤ 2 s Mean afterglow ≤ 2 s
6.8	Impact of spatter	15 drops	25 drops
6.9	Heat transfer (radiation)	RHTI 24 W 7	RHTI 24 W 16
6.10	Electrical resistance	$> 10^5 \Omega$	$> 10^5 \Omega$
6.11	Innocuousness	See 6.11	See 6.11

^a For ISO 15025:2000, Procedure B, this requirement is not applicable

Testing and certification of this product is done according to EN ISO 11611:2015 by TÜV Rheinland LGA Products GmbH, Tillystraße 2, D-90431 Nürnberg, Germany (notified body number 0197).



Test reports, certificates and manuals can be downloaded from: www.weldas-ce.com